



Pasos

Pasos de roscas P en mm para

- (1) Rosca normal métrica ISO M
- (2) Rosca fina métrica ISO M-F
- (3) Rosca trapezoidal Tr

Número de hilos por pulgada para

- (4) Rosca normal UNC/ Unified National Coarse thread
- (5) Rosca fina UNF/ Unified National Fine thread
- (6) Rosca BSW/ Rosca británica Whitworth paso normal.
- (7) Rosca fina BSF (Norma británica paso fino)
- (8) Rosca de tubo Whitworth

															
Rosca		1	2			3		Rosca			4	5	6	7	8
M	Tr	M	M-F *	M-F2	M-F3	Tr *		UNC/UNF Nr.	Pulgada	Métrico mm	UNC (NC)	UNF (NF)	BSW (Ww c)	BSF (Ww F)	R, G Rp, Rc
1		0,25	(0,2)					0		1,524	-	80	-	-	-
1,2		0,25	(0,2)					1		1,854	64	72	-	-	-
1,4		0,3	(0,2)					2		2,184	56	64	-	-	-
1,6		0,35	(0,2)					3		2,515	48	56	-	-	-
1,8		0,35	(0,2)					4		2,845	40	48	-	-	-
2		0,4	(0,25)					5		3,175	40	44	-	-	-
2,2		0,45	(0,25)					6		3,505	32	40	-	-	-
2,5		0,45	(0,35)					8		4,166	32	36	-	-	-
3		0,5	(0,35)					10		4,826	24	32	-	-	-
3,5		0,6	(0,35)					12		5,486	24	28	-	-	-
4		0,7	0,5						1/8	3,175	40	44	40	-	28
5		0,8	0,5						5/32	3,969	32	36	32	-	-
6		1	0,75	0,5					3/16	4,763	24	32	24	32	-
8	8	1,25	1	0,75	0,5	1,5			7/32	5,556	24	28	-	28	-
10	10	1,5	1,25	1	0,75	2	1,5		1/4	6,350	20	28	20	26	19
12	12	1,75	1,5	1,25	1	3	2		5/16	7,938	18	24	18	22	-
14	14	2	1,5	1,25	1	4	3	2	3/8	9,525	16	24	16	20	19
16	16	2	1,5		1		4	2	7/16	11,113	14	20	14	18	-
18	18	2,5	2	1,5	1		4	2	1/2	12,700	13	20	12	16	14
20	20	2,5	2	1,5	1		4	2	9/16	14,288	12	18	12	16	-
22	22	2,5	2	1,5	1	8	5	3	5/8	15,875	11	18	11	14	14
24	24	3	2	1,5	1	8	5	3	3/4	19,050	10	16	10	12	14
27	26/28	3	2	1,5	(1)	8	5	3	7/8	22,225	9	14	9	11	14
30	30	3,5	2	1,5	(1)	10	6	3	1	25,401	8	12	8	10	11
33	32/34	3,5	2	1,5		10	6	3	1 1/8	28,575	7*	12	7	9	11
36	36	4	3	2	1,5	10	6	3	1 1/4	31,750	7*	12	7	9	11
39	38/40	4	3	2	1,5	10	7	3	1 3/8	34,925	6*	12	6	8	11
42	42	4,5	(4)3	2	1,5	10	7	3	1 1/2	38,100	6*	12	6	8	11
45	44/46	4,5	(4)3		1,5	12	7/8	3	1 3/4	44,450	5*	12	5	7	11
48	48	5	(4)3	2	1,5	12	8	3	2	50,802	4 1/2*	12	4 1/2	7	11
52	50/52	5	(4)3	2	1,5	12	8	3	2 1/4	57,150	4 1/2*	-	4	-	11
56	55	5,5	4	3/2	1,5	14	9	3	2 1/2	63,500	4*	-	4	-	11
60	60	5,5	4	3/2	1,5	14	9	3	2 3/4	69,850	4*	-	3 1/2	-	11
64	65	6	4	3	2(1,5)	16	10	4	3	76,200	4*	-	3 1/2	-	11
68	70	6	4	3	2(1,5)	16	10	4	4	101,60	4*	-	3	-	11
Flancos ↗		60°			30°		-		60°		55°				
*de uso preferente								*Espárragos diámetro ≥ 1" = ¡constante 8 pulgadas!							
								** las roscas de tubo tienen diámetro exterior mayor (=> cuadro 5)							